

# NanoSeal GT

## Tile Sealer

# Maintenance

## Procedures

This document outlines the general maintenance practices and does not address any post-application finishing that may require specific care.

### Spills

Wipe up all spills immediately with a damp cloth.

### Cleaning

Dust mop regularly to maintain a dust-free, slip-resistant surface. Where deeper cleaning is required, use a new/clean microfibre mop with a 1:32 – 1:48 dilution of NeutraClean GT concentrate (refer to instructions on packaging). It is not recommended to use an of automatic scrubber.

- ⚠ **Never use abrasive pads or hard-bristle brushes.**
- ⚠ **Never use acidic cleaners or strippers.**

Other PH neutral cleaners may be acceptable. Be sure to test in an inconspicuous area first.

### Small Localized Scratches

For small scratches, polish out with a white pad and then wipe clean.

- ⚠ **Do not use soaps or detergents as this may damage the topcoat of NanoSeal GT.**

Let the area dry for 24 hours and then apply a thin coat of NanoSeal GT as per the application instructions.

### Large Scratches

For large scratches, polish out the entire scratched area with a white pad and then wipe clean using a damp microfibre cloth.

- ⚠ **Do not use soaps or detergents as this may damage the topcoat of NanoSeal GT.**

Let the area dry for 24 hours and then apply a thin coat of NanoSeal GT to the entire surface area as per the application instructions.

### Scratch Prevention

Use walk-off mats in inclement weather.

- ⚠ **Do not leave wet mats or other fabrics on surface for extended periods of time.**

Use felt pads on furniture bases. Use chair mats for all types of chairs.

### Deep Gouges

If gouging or other damage has occurred to the tile, wipe the area clean using a damp microfibre clot. After drying for 24 hours, Once dry, spot retouch the damaged area with NanoSeal GT.

### Warranty

Subject to Geon Tile Ltd. limited warranty. For copies and further information, visit geontile.com.